Specifications maharam Scuba

Application

464930

Seating

Upholstered Walls require additional finishes.

Not approved for pool areas.

Note: Use with discretion in food service environments, as strict adherence to cleaning protocol is required.

Characteristics

Content: 100% Polyurethane

Finish: None Backing: Polyester Width: 54" (137cm) Bolt Size: 35 yards (32 m) Weight: 20 oz/ly (620 gr/lm) Country of Origin: Korea

Price

Contact your sales representative for pricing.

Maintenance

W/B-Clean with water-based cleanser or diluted household bleach.

Testing

Abrasion: ASTM D4966, 200,000 cycles Martindale

Note: Abrasion test results exceeding ACT Performance Guidelines are not an indicator of product lifespan. Multiple factors affect fabric durability and appearance retention.

Flammability: AS/NZS 1530.3 AS/NZS 3837 Unadhered BS 5852 Crib 5* CAL 117-2013 DIN 4102* EN 1021-1* EN 1021-2* GB/T 17591* NFPA 260

*passes with additional treatment

Lightfastness: AATCC 16E, 200+ hours

△ * * * • *

UNI 9175*

Specifications maharam Scuba

Environmental

464930

Greenguard Gold Certified Healthier Hospitals Compliant LBC Red List Free Produced in an ISO 14001 Facility FR Free PFAS-Free

Warranty

5 years.

© 2007 Maharam

Complete product information at maharam.com 800.645.3943

