

pelle / soft -leather / Softleder / peau / piel

Seta

Application

Offices, hotels, institutions,
domestic use.

Description

Thickness 1,3 - 1,5 mm
Bovine hides, EU
Natural grain
Solid tone
Mineral chrome tanning
Through-dyeing aniline
Semi aniline finish

Tests

Colour fastness to light
xenotest, ≥ 4 Blue Scale
UNI EN ISO 105-B02

Samples are purely indicative because of
natural inconsistencies that occur in the
raw materials. As a result there may be
small differences in the product delivered.

Colour fastness to -and-fro rubbing
80 alk. perspiration cycles, $\geq 3/4$
degradation and staining Grey scale
UNI EN ISO 11640-11641

Tear Strenght
 ≥ 20 N
UNI EN ISO 3377-1
Flexing endurance
dry, ≥ 20000 cycles
UNI EN ISO 5402

Cold crack resistance of finish
 -15°C , no crack
UNI EN ISO 17233


Fire resistance
UNI EN 1021-1 No ignition

Leather is a natural material therefore
small imperfections cannot be considered
quality issues but peculiar characteristics
of the materials.


UNI EN 1021-2 No ignition
BS 5852/0 cigarette test No ignition
BS 5852/1 match test No ignition

Care

For a normal cleaning we suggest to dust
with a soft and dry cloth. Any stain can be
removed using a damp cloth and delicate
cleaning products such as a neutral soap or
detergent. Do not wipe the surface but just
buffer from the edges to the stain centre. It
is absolutely forbidden to use abrasive or
aggressive products such as solvents, stain
removers etc. Do not use steam. For the
most resistant stains contact the supplier.
Avoid placing leather in direct sun. Keep the
leather away from the direct heat.




9000
Latte




9012
Zenzero



9018
Bird



9020
Tartufo




9022
Minerale



9049
Custard



9001
Dalia




9063
Acero



9006
Teak



9004
Mattone



9009
Acacia



9030
Cardamomo



9015
Carrara




9016
Elefante



9036
Oltremare



9073
Novembre



9033
Pepe